



TECHNICAL DATA

MANUS-BOND 64A-TRIM Tape

1. PRODUCT DESCRIPTION:

Manus Bond 64A-TRIM Tape is 100% solids preformed synthetic polymer based adhesive/tape. 64A-TRIM Tape has excellent adhesion to metals, glass, plastics and other porous and non porous surfaces. Adhesion improves with age and remains permanently flexible, even at low temperatures. This product is designed for sealing lap joints. Excess tape is easily trimmed away to provide a neat and clean application.

2. TECHNICAL DATA:

Property	Test Method	Typical Value
Color	Visual	White
Solids Content	ASTM C 681	100%
Specific Gravity	ASTM D 71	1.55
Weight per Gallon	ASTM D 71	12.93 lbs.
Cone Penetration Hardness	ASTM D 217	100
Shear Strength		pending
Peel Strength via Climbing Drum	ASTM D1781	12 lbs.
Service Temperature	ASTM D 3359	-60°F—212°F
Shelf Life		1 year minimum when stored at or below 80°F

Note: All statements and information contained herein is published as general information only and is accurate to the best of our knowledge.

**MANUS PRODUCTS INC.
MPI**

866 INDUSTRIAL BLVD WEST • WACONIA, MINNESOTA 55387
PHONE: (952) 442-3323
FAX: (952) 442-3327
EMAIL: info@manus.net
www.manus.net