



# TECHNICAL DATA

## MANUS-BOND™ 75-AM XTREME

### 1. PRODUCT DESCRIPTION:

Manus-Bond™ 75-AM Xtreme is based on an advanced, hybrid silylated prepolymer. This hybrid system overcomes the limitations of typical polyurethanes without sacrificing performance. 75-AM Xtreme does not contain solvents or isocyanates. It is non-yellowing. 75-AM Xtreme offers superior primerless adhesion to large variety of substrates and has excellent paintability. It exhibits low dirt pick-up, cures fast, and is non-staining on porous surfaces. 75-AM Xtreme has exceptional UV resistance and is highly durable even in the harshest environments, including chemical resistance to jet fuels and road salts. Conforms to TTS-0230C and ASTM C920-02, for Type S, Grade NS, Class 100, Use NT, G, A, and M. USDA accepted.

### 2. TECHNICAL DATA:

Specific Gravity	1.50-1.54
Skin Time (minutes) 75°F 50% RH	20-30
Viscosity (cps) Spindle T-E at 5 rpms	500,000 cps
% Elongation *Rate = 2"/minute	350%
Tensile Strength *Rate = 2"/minute	180 psi
100% Modulus	75 psi
Hardness Shore A	35-45
Service Temperature	-75°F to 350°F

3. **PACKAGING:**

10.1 fl.oz. cartridge, 5 gallon and 55 gallon containers. Other packaging options available.

4. **SURFACE PREPARATION:**

Apply to clean, dry surfaces free of contaminants that can adversely affect adhesion. Remove all old sealant before applying Manus-Bond™ 75-AM Xtreme. Testing a small area for compatibility is recommended.

5. **PAINTING:**

Cured product may be painted with most industrial & consumer paints. Testing prior to painting is recommended.

6. **STORAGE LIFE:**

For maximum shelf life, store unopened product at or below 80°F.  
12 months = cartridges  
6 months = 5 and 55 gallon containers

7. **PRECAUTIONS:**

Some applications may not be compatible with this product. Testing suitability for intended application before proceeding with full application is recommended. Use with adequate ventilation. Inhalation of vapor during application and cure may cause slight eye or throat irritation. In case of contact with eyes, lips, or mouth, flush thoroughly with water. If irritation persists, consult a physician. Avoid repeated, prolonged contact with skin. See MSDS for additional information. **KEEP OUT OF REACH FROM CHILDREN.**

8. **TECHNICAL SERVICE:**

Manus technical representatives are always available to provide assistance. Please contact our Technical Service Department with your questions or requests for specific applications.

9. **LIMITED WARRANTY:**

Any goods prove defective will be replaced or the purchase price refunded. The limited warranty described herein is in lieu of any other warranty, expressed or implied, including any implied warranty of merchantability or fitness for a particular use. The user shall determine suitability of the product for its intended use. Liability for any incidental or consequential damage or loss is excluded. The user assumes all risks of the product's use, handling and storage.

**MANUS PRODUCTS INC.**  
**MPI**

866 INDUSTRIAL BLVD WEST • WACONIA, MINNESOTA 55387  
PHONE: (952) 442-3323  
FAX: (952) 442-3327  
EMAIL: [info@manus.net](mailto:info@manus.net)  
[www.manus.net](http://www.manus.net)